

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
24 December 2003 (24.12.2003)

PCT

(10) International Publication Number
WO 03/106207 A1

(51) International Patent Classification⁷:
B60K 7/00, 17/04, 17/08, H02K 7/116, F16H 57/04

B60K 7/00,

(74) Agent: LUNT, Mark, George, Francis; Harrison Goddard Foote, Fountain Precinct, Leopold Street, Sheffield S1 2QD (GB).

(21) International Application Number: PCT/GB03/02619

(22) International Filing Date: 18 June 2003 (18.06.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0213944.2 18 June 2002 (18.06.2002) GB

(71) Applicant (for all designated States except US): **MAGNETIC SYSTEMS TECHNOLOGY LIMITED** [GB/GB]; 60 Shirland Lane, Sheffield S9 3SP (GB).

(72) Inventor; and


(75) Inventor/Applicant (for US only): **JENKINS, Marcus** [GB/GB]; 60 Shirland Lane, Sheffield S9 3SP (GB).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: HUB DRIVE SYSTEM



(57) Abstract: A hub drive (10) has a tubular housing (12) suspended in a vehicle, and a motor (22) in one, inboard end of the housing, and a gearbox (36) in the other end. A hub (40) is driven by the gearbox and is journaled on the housing. A gallery (89) is defined between the motor and housing to receive lubricant from an external connector (96) to cool the motor before delivery via a passage (92) to a rotor (28) of the motor, and thence to the gearbox to lubricate the gearbox. The drive is dismantlable without removal of the vehicle wheel, from the open ends (18, 20) of the housing. A gear change mechanism (50) permits minimisation of the motor while still providing a wide range of torque and speed capability.